Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: UZIN ER 200 Komp. A

• Application of the substance / the preparation 2-Component Epoxy Binding Agent (Component A)

- Manufacturer/Supplier: UZIN Ltd. 7/8 Cholswell Court Shippon Abingdon, OX 13 6 HW Tel. 01235/53 41 06 Fax 01235/53 41 07
- Further information obtainable from: Product safety department email: msds.info@uzin-utz.com • Information in case of emergency:
- Medical emergencies: +49 30 30 686 790 Transportation emergencies: +49 621 60 43 333

2 Hazards identification

• Hazard description:



Xi Irritant N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains epoxy constituents. See information supplied by the manufacturer.

3 Composition/information on ingredients

· Chemical characterization

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number	75-100%
NLP: 500-033-5	average molecular weight ≤ 700)	
	🗙 Xi, 🦐 N; R 36/38-43-51/53	
	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10 - <25%
EINECS: 271-846-8	🗙 Xi, 🧓 N; R 36/38-43-51/53	
· Additional informati	ion. For the wording of the listed risk phrases refer to section 16	

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

· General information: Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 2)

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

(Contd. of page 1)

Trade name: UZIN ER 200 Komp. A

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- \cdot Measures for cleaning/collecting:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

7 Handling and storage

· Handling:

· Information for safe handling:

Immediately remove all soiled and contaminated clothing Wear suitable protective clothing, gloves and eye/face protection.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

- · Information about fire and explosion protection: No special measures required.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wear suitable protective clothing, gloves and eye/face protection. Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin. Wash hands before breaks and at the end of work.
- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

(Contd. on page 3)

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

(Contd. of page 2)

Trade name: UZIN ER 200 Komp. A

• Material of gloves

Butyl rubber, BR Nitrile rubber, NBR

• **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information	
Form:	Fluid
Colour:	Yellowish
Odour:	Weak, characteristic
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	> 100°C
· Ignition temperature:	>200°C
· Self-igniting:	Product is not selfigniting.
• Danger of explosion:	Product does not present an explosion hazard.
· Density at 20°C:	1.1 g/cm ³
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Viscosity: Dynamic at 20°C:	1000 mPas

10 Stability and reactivity

• *Thermal decomposition / conditions to be avoided:* No decomposition if used according to specifications. • *Dangerous reactions*

May produce violent reactions with bases and numerous organic substances including alcohols and amines. Exothermic polymerization.

• Dangerous decomposition products: At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.

(Contd. on page 4)

GB

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

(Contd. of page 3)

Trade name: UZIN ER 200 Komp. A

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological information

· Ecotoxical effects:

• Remark: Toxic for fish

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

· Product:

· Recommendation

The product contains materials that are harmful to the environment. Do not allow product to reach ground water, water course or sewage system. Mix both product components, allow to harden, then dispose of as construction waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14 Transport information

· Land transport ADR/RID (cross-border)

· ADR/RID class:	9 Miscellaneous dangerous substances and articles.
· Danger code (Kemler)	: 90
· UN-Number:	3082
· Packaging group:	III
· Hazard label	9
• Description of goods:	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epox resin)
14	
• Maritime transport IM	IDG:
Maritime transport IM	IDG:
• Maritime transport IM	9
• IMDG Class:	9
• IMDG Class: • UN Number: • Label	9 3082
• IMDG Class: • UN Number:	9 3082 9

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

Trade name: UZIN ER 200 Komp. A

.	(Contd. of page
	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
• Air transport ICAO-TI	and IATA-DGR:
· ICAO/IATA Class: · UN/ID Number:	9 3082
· Label	9
· Packaging group:	III : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
· Froper snipping name.	ENVIKONMENTALLI HAZAKDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resul)
Regulatory inform	ation
· Labelling according to	EU guidelines:
	classified and marked in accordance with EU Directives / Ordinance on Hazardo
	designation of product:
Xi Irritant N Dangerous for the end	nvironment
• Hazard-determining co reaction product: bisph	<i>Supponents of tabeling:</i> $menol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)$
· Risk phrases:	
36/38 Irritating to eyes43 May cause sensit	and skin. tisation by skin contact.
	organisms, may cause long-term adverse effects in the aquatic environment.
\cdot Safety phrases:	
24/25 Avoid contact wi	
	rt with eyes, rinse immediately with plenty of water and seek medical advice. th skin, take off immediately all contaminated clothing, and wash immediately w
plenty of water a	nd soap.
	oves and eye/face protection.
	the environment. Refer to special instructions/safety data sheets.
• Special labelling of cer Contains epoxy constitu	rtain preparations: uents. See information supplied by the manufacturer.
Other information	
	sed on our present knowledge. However, this shall not constitute a guarantee for a es and shall not establish a legally valid contractual relationship.
· Relevant R-phrases	
36/38 Irritating to eyes43 May cause sensit	and skin. tisation by skin contact.
	organisms, may cause long-term adverse effects in the aquatic environment.
	SDS: Product safety department
· Department issuing M	
• Department issuing M. • Contact:	

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

1 Identification of the substance/preparation and of the company/undertaking · Product details · Trade name: UZIN ER 200 Komp. B • Application of the substance / the preparation 2-Component Epoxy Binding Agent (Component B) · Manufacturer/Supplier: UZIN Ltd. 7/8 Cholswell Court Shippon Abingdon, OX 13 6 HW Tel. 01235/53 41 06 Fax 01235/53 41 07 · Further information obtainable from: Product safety department email: msds.info@uzin-utz.com · Information in case of emergency: Medical emergencies: +49 30 30 686 790 Transportation emergencies: +49 621 60 43 333 2 Hazards identification · Hazard description: C Corrosive N Dangerous for the environment · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed. R 34 Causes burns. R 43 May cause sensitisation by skin contact. R 62 Possible risk of impaired fertility. R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R 63 Possible risk of harm to the unborn child. **3** Composition/information on ingredients · Chemical characterization • Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: CAS: 100-51-6 Benzyl alcohol 25-50% EINECS: 202-859-9 🗙 Xn; R 20/22 CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine 25-50% EINECS: 220-666-8 🛃 C, 🗙 Xn; R 21/22-34-43-52/53 CAS: 25154-52-3 nonylphenol 10 - <25% EINECS: 246-672-0 Repr. Cat. 3; 🖪 C, 🗙 Xn, 🌄 N; R 22-34-62-50/53-63 • Additional information: For the wording of the listed risk phrases refer to section 16. **4** First-aid measures · General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately wash with water and soap and rinse thoroughly. • After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

(Contd. of page 1)

Trade name: UZIN ER 200 Komp. B

· After swallowing: Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO2 powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- · Person-related safety precautions:
- Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- *Measures for cleaning/collecting:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

7 Handling and storage

· Handling:

- Information for safe handling: Immediately remove all soiled and contaminated clothing Wear suitable protective clothing, gloves and eye/face protection. Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin. Wash hands before breaks and at the end of work.
- · Information about fire and explosion protection: No special measures required.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wear suitable protective clothing, gloves and eye/face protection. Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin. Wash hands before breaks and at the end of work.

· Respiratory protection: Not necessary if room is well-ventilated.

(Contd. on page 3)

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

(Contd. of page 2)

Trade name: UZIN ER 200 Komp. B

· Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

• **Material of gloves** Butyl rubber, BR Nitrile rubber, NBR

• **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

General Information	
Form:	Fluid
Colour:	Yellowish
Odour:	Fish-like
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	> 100°C
Ignition temperature:	> 200°C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Vapour pressure at 20°C:	ca. 15 hPa
Density at 20°C:	1 g/cm ³
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
pH-value at 20°C:	11
Viscosity:	
Dynamic at 20°C:	100 mPas

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Dangerous reactions Strong exothermic reaction with acids.
- Dangerous decomposition products: At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

(Contd. on page 4)

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

Trade name: UZIN ER 200 Komp. B

(Contd. of page 3)

LD/LC5	50 valu	es relevant for classification:
100-51-	6 Benz	yl alcohol
Oral	LD50	1230 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
25154-5	2-3 no	nylphenol
Oral	LD50	1620 mg/kg (rat)

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful Irritant

Corrosive

12 Ecological information

· Ecotoxical effects:

· Remark: Toxic for fish

· General notes:

Do not allow product to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

13 Disposal considerations

· Product:

The product contains materials that are harmful to the environment. Do not allow product to reach ground water, water course or sewage system. Mix both product components, allow to harden, then dispose of as construction waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 8 Corrosive substances.

• Danger code (Kemler): 80

• UN-Number: 2289

• Packaging group: III

(Contd. on page 5)

[·] Recommendation

GB

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

Trade name: UZIN ER 200 Komp. B

Hazard label	8	
-	2289 ISOPHORONEDIAMINE, mixture	
· Maritime transport IM		
· IMDG Class:	8	
· UN Number:	2289	
· Label	8	
· Packaging group:	III	
• EMS Number:	F-A, S-B	
• Marine pollutant:	No	
	: ISOPHORONEDIAMINE, mixture	
• Air transport ICAO-TA		
· ICAO/IATA Class:	8	
· UN/ID Number:	2289	
· Label	8	
· Packaging group:	III	
· Proper shipping name	: ISOPHORONEDIAMINE, mixture	
Regulatory inform		

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- Code letter and hazard designation of product: C Corrosive N Dangerous for the environment
- *Hazard-determining components of labelling:* 3-aminomethyl-3,5,5-trimethylcyclohexylamine Benzyl alcohol nonylphenol

· Risk phrases:

- 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- 34 Causes burns.
- 43 May cause sensitisation by skin contact.
- 62 *Possible risk of impaired fertility.*
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 63 Possible risk of harm to the unborn child.

· Safety phrases:

- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 27/28 After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
- 37/39 Wear suitable gloves and eye/face protection.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

(Contd. on page 6)

GB -

Printing date 13.08.2008

Version No. 1

Revision: 13.08.2008

Trade name: UZIN ER 200 Komp. B

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

(Contd. of page 5)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

20/22 Harmful by inhalation and if swallowed.

- 21/22 Harmful in contact with skin and if swallowed.
- 22 Harmful if swallowed.
- 34 Causes burns.
- 43 May cause sensitisation by skin contact.

50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
62 Possible risk of impaired fertility.

- 63 Possible risk of harm to the unborn child.
- · Department issuing MSDS: Product safety department

· Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207 *E-Mail: msds.info@uzin-utz.com*

GB -