1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: UZIN VE 100

· Application of the substance / the preparation Solvent Thinner for Neoprene

· Manufacturer/Supplier:

UZIN Ltd.

7/8 Cholswell Court Shippon Abingdon, OX 13 6 HW Tel. 01235/53 41 06 Fax 01235/53 41 07

· Further information obtainable from:

Product safety department email: msds.info@uzin-utz.com

· Information in case of emergency:

Medical emergencies: +49 30 30 686 790 Transportation emergencies: +49 621 60 43 333

2 Hazards identification

· Hazard description:







Xn Harmful

F Highly flammable

N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 11 Highly flammable.

R 18 In use, may form flammable/explosive vapour-air mixture.

R 36/38 Irritating to eyes and skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

3 Composition/information on ingredients

- · Chemical characterization
- · Description:

Solvent Thinner

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 92062-15-2 EINECS: 295-529-9	Solvent naphtha (petroleum), hydrotreated light naphthenic \mathbf{X} Xn, \mathbf{X} Xi, \mathbf{B} F, \mathbf{E} N; R 11-38-51/53-65-67	50-75%
	ethyl acetate	25-50%

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

Trade name: UZIN VE 100

(Contd. of page 1)

· After swallowing: Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

· Suitable extinguishing agents:

CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards caused by the substance, its products of combustion or resulting gases: Can form explosive gas-air mixtures.
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling:

Immediately remove all soiled and contaminated clothing

Wear suitable protective clothing, gloves and eye/face protection.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wear suitable protective clothing, gloves and eye/face protection.

(Contd. on page 3)

Trade name: UZIN VE 100

(Contd. of page 2)

 ${\it Keep \ away \ from \ foodstuffs, \ beverages \ and \ feed.}$

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary in well ventilated areas or areas with local exhaust ventilation (e.g. ex-protected ventilation / evacuation equipment).

In case of prolonged exposition in poorly ventilated areas, e.g. in closed rooms, use ambient air-independent breathing apparatus.

· Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information	
Form:	Fluid
Colour:	Colourless
Odour:	Solvent-like
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	77°C
· Flash point:	-I°C
· Ignition temperature:	460°C
· Self-igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20°C:	97 hPa
· Density at 20°C:	0.95 g/cm³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 4)

Trade name: UZIN VE 100

(Contd. of page 3)

- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system.

Disposal should be in accordance with local, state or national legislation.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

Danger code (Kemler): 33
UN-Number: 1993
Packaging group: II
Hazard label 3

(Contd. on page 5)

Trade name: UZIN VE 100

(Contd. of page 4)

· Description of goods: 1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (ETHYL ACETATE,

Solvent naphtha)

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 1993
· Label 3
· Packaging group: II
· EMS Number: F-E,S-E
· Marine pollutant: No

· Proper shipping name: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, Solvent naphtha (petroleum),

hydrotreated light naphthenic)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1993 · Label 3 · Packaging group: II

· Proper shipping name: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, Solvent naphtha (petroleum),

hydrotreated light naphthenic)

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xn Harmful

F Highly flammable

N Dangerous for the environment

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), hydrotreated light naphthenic

· Risk phrases:

- 11 Highly flammable.
- 18 In use, may form flammable/explosive vapour-air mixture.

36/38 Irritating to eyes and skin.

- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 24/25 Avoid contact with skin and eyes.
- 37 Wear suitable gloves.
- 51 Use only in well-ventilated areas.

(Contd. on page 6)

Trade name: UZIN VE 100

(Contd. of page 5)

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 11 Highly flammable.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department
- · Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207

E-Mail: msds.info@uzin-utz.com

GB